AMENDMENTS TO THE CLAIMS

Please cancel claims 20 and 21, and amend the remaining claims as set forth in the following listing of claims. This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

- 1. (Currently Amended) A secondary electrochemical cell with an alkaline electrolyte, the cell containing a positive non-sintered electrode comprising a <u>substantially flat plane form</u> two-dimensional conductive support covered in a layer containing nickel hydroxide and a binder, wherein said binder is a mixture of a cellulose compound and a styrene-acrylate copolymer which is a combination of elementary styrene units (-CH₂CHC₆H₅.), and of elementary acrylic ester or acrylate units (-CH₂CHCOOR-), wherein said two dimensional conductive support has a thickness of between 10⁻² mm and 10⁻¹ mm.
- (Previously Presented) A cell according to claim 1, in which the proportion of said styrene-acrylate copolymer is less than 4% by weight of said layer.
- (Previously Presented) A cell according to claim 2, in which the proportion of said styrene-acrylate copolymer lies in the range 0.15% to 3% by weight of said layer.

Amendment Under 37 CFR 1.1111 USSN 10/774.614

(Previously Presented) A cell according to claim 1, in which said cellulose compound is selected from methylcellulose, carboxymethylcellulose, hydroxypropylmethyl-cellulose, hydroxypropylcellulose, and hydroxyethylcellulose.

 (Previously Presented) A cell according to claim 1, in which the proportion of said cellulose compound lies in the range 0.1% to 1% by weight of said layer.

6. (Canceled)

- 7. (Previously Presented) A cell according to claim 1, in which said nickel hydroxide also contains at least one syncrystallized hydroxide of an element selected from zinc, cadmium, and magnesium, and at least one syncrystallized hydroxide of an element selected from cobalt, manganese, aluminum, vttrium, calcium, strontium, zirconium, copper.
- 8. (Previously Presented) A cell according to claim 1, in which said nickel hydroxide has a spheroidal shape and has a grain size lying in the range 7 μ m to 20 μ m.
- (Previously Presented) A cell according to claim 1, in which said layer also comprises a conductive material consisting principally of a compound of cobalt.
- 10. (Previously Presented) A cell according to claim 9, in which said compound of cobalt is selected from cobalt metal Co, cobalt oxide CoO, cobalt hydroxide Co(OH)₂, the

composite oxide of lithium and cobalt LiCoO2, and an oxide of conductive cobalt oxide of a valency greater than 2.

- 11. (Previously Presented) A cell according to claim 1, in which said layer also contains at least one other compound selected from the compounds of zinc, yttrium, ytterbium, and calcium.
- 12. (Previously Presented) A cell according to claim 11, in which said compound is a compound of yttrium.
- (Previously Presented) A cell according to claim 12, in which said compound of yttrium is selected from yttrium oxide Y₂O₃ and yttrium hydroxide Y(OH)₃.
- 14. (Previously Presented) A cell according to claim 11, in which said compound is a compound of ytterbium.
- 15. (Previously Presented) A cell according to claim 14, in which said compound of ytterbium is selected from ytterbium oxide Yb₂O₃ and ytterbium hydroxide Yb(OH)₃.
- 16. (Previously Presented) A cell according to claim 1, in which said layer also contains polymer fibers.

Amendment Under 37 CFR 1.1111 USSN 10/774,614

17. (Previously Presented) A cell according to claim 1, in which said two-dimensional

conductive support is selected from a solid or a perforated strip, an expanded metal, a grid, and a

fabric.

18. (Previously Presented) A cell according to claim 1, also comprising a metal-hydride

negative electrode.

19. (Previously Presented) A cell according to claim 1, wherein said binder consists of

said mixture.

20. (Canceled)

21. (Canceled)

5